

Black Rhino™ Flex 700 NE

High Speed Near Edge Thermal Transfer Resin Ribbon

A thermal transfer ribbon that is designed precisely for online date coders and some near edge desktop applications where exceptional performance in harsh labeling environments and high volume labeling applications is essential. Developed for flexible packaging applications that require increased smudge and scratch resistance, BR-Flex 700 NE offers remarkable performance characteristics on synthetic paper film.



Black Rhino™ Printer Supplies

Black Rhino™ Thermal Transfer Ribbons

Wax Thermal Transfer Ribbons

Wax/Resin Thermal Transfer Ribbons

Resin Thermal Transfer Ribbons

Near Edge Thermal Transfer Ribbons

Tech Specs

	Ribbon Thickness	Printing Density	Transmission Density	Ink Melting Point
Flex 700 NE Black	< 9.0 micron	> 1.80 Macbeth Scale	> 0.90 Macbeth Scale	70° C (158° F)

Performance Characteristics:

- Low printhead energy
- Abrasion/scratch resistance
- Chemical resistance to common agents
- Print flexibility
- High density print
- High speed
- Anti-static coating for printhead protection

Recommended Substrates:

Synthetic: LDPE, MDPE, PET, PVC

Recommended Applications:



Flex Packaging



Fresh Fruit/Produce



Retail



Healthcare



Pharmaceutical

PRODUCT DISCLAIMER

Testing under end-user conditions is always recommended to ensure the selected ribbon formulation is suitable for specific application requirements.