

Material Specification Sheet**Product:**

Clean Release - Inkjet

Description:

A topcoated, biaxially oriented, semi gloss, white polypropylene film uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon with a water-based acrylic all temperature PSA formulation and a semi-bleached, supercalendered white kraft suitable for roll-label applications.

Recommended Applications:

For applications needing aggressive performance at low temperatures and is well suited for refrigerated food label applications. Conforms to FDA 175.105 for indirect food contact and CONEG regulations.

Facestock:

A topcoated, biaxially oriented, semi gloss, white polypropylene film uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.

	<u>Value</u>	<u>Units</u>
Caliper:	3.1	mil

Adhesive:

A water-based acrylic all-temperature permanent PSA formulation. Adhesive is both latex and elementally chlorine free.

	<u>Value</u>	<u>Units</u>
Application temp:	-20°	Fahrenheit
Service temp:	-30° to +200°	Fahrenheit

Liner:

A 40# semi-bleached, supercalendered white kraft suitable for roll-label applications.

	<u>Value</u>	<u>Units</u>
Caliper:	2.5	mil
Tensile: MD	34	lb/in ²
CD	22	lb/in ²
Tear: MD	32	grams
CD	34	grams
Opacity:	65	percent

Shelf Life:

One year, under standard storage and humidity conditions

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

