

Material Specification Sheet**Product:**

M-728

Description:

A thermal transfer matte PET film facestock with a permanent pressure sensitive acrylic adhesive and a semi bleached kraft liner.

Recommended Applications:

This material is recommended for the pharmaceutical industry. It is UL recognized for indoor and outdoor use.

Facestock:

A matte thermal transfer PET film facestock.

	<u>Value</u>	<u>Units</u>
Thickness:	3.0 ± 15%	mil

Adhesive:

A permanent, pressure sensitive acrylic adhesive.

	<u>Value</u>	<u>Units</u>
Thickness:	0.9-1.0 ± 0.1	mil
Minimum Application Temp:	50	°F
Service Temp:	-40 to +302	°F
Expected Shear:	60	hours
Adhesion:		
Stainless Steel	91	oz/in
Glass	93	oz/in
Polypropylene	13	oz/in
Acrylic	76	oz/in
Tack:	970	g

Liner:

A semi bleached kraft liner.

	<u>Value</u>	<u>Units</u>
Thickness:	3.1 ± 10%	mil

Shelf Life:

One year, under standard storage and humidity conditions

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

