

---

**Material Specification Sheet****Product:**

M-750

**Description:**

A matte white top coated thermal transfer polyimide film facestock with a high temp permanent acrylic adhesive and a supercalendered silicone coated release kraft liner.

**Recommended Applications:**

This material is recommended for high temp, lead-free solder applications. It is the ideal label to withstand surface mount board processes or other manufacturing processes where dimensional stability of the label is critical.

---

**Facestock:**

A matte white top coated thermal transfer polyimide film facestock.

	<u>Value</u>	<u>Units</u>
Caliper:	1.0	mil

**Adhesive:**

A high temp permanent acrylic adhesive.

	<u>Value</u>	<u>Units</u>
Service temp:	-40 to +1,000	°F

**Liner:**

A supercalendered silicone coated release kraft liner.

		<u>Value</u>	<u>Units</u>
Basis Weight:		40	lbs/ream
Caliper:		2.5	mil
Tensile:	MD	39	lbs/in
	CD	19	lbs/in
Tear:	MD	42	grams
	CD	44	grams

**Shelf Life:**

One year, under standard storage and humidity conditions

**PRODUCT DISCLAIMER**

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

