

---

**Material Specification Sheet****Product:**

M-787

**Description:**

A thermal transfer gloss white polyester facestock with an acrylic adhesive and a densified kraft liner.

**Recommended Applications:**

This material is recommended for applications that require durability.

---

**Facestock:**

A thermal transfer gloss white polyester facestock that has a topcoat for improved ink receptivity.

	<u>Value</u>	<u>Units</u>
Caliper:	2.0	mil

**Adhesive:**

An acrylic adhesive that offers excellent UV and chemical resistance. Can permanently bond to high surface energy and low surface energy plastics, powder coatings, slightly oily metals, and textured and contoured surfaces.

	<u>Value</u>	<u>Units</u>
Minimum Application temp:	-40	°F
Service temp:	-65 to +300	°F
180° Peel:		
Stainless Steel	88	oz/in
Glass	93	oz/in
HD Polyethylene	54	oz/in
LD Polyethylene	53	oz/in
Polycarbonate	90	oz/in
Polypropylene	73	oz/in
Glass	93	oz/in

**Liner:**

A densified kraft liner that allows for good die cutting.

	<u>Value</u>	<u>Units</u>
Caliper:	3.2	mil

**Shelf Life:**

One year, under standard storage and humidity conditions

**PRODUCT DISCLAIMER**

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

